

Polarization Maintaining Fused Wavelength Division Multiplexer (PMWDM)

Specialist in Special Optic Devices

Introduction

Beamq Polarization Maintaining Fused Wavelength Division Multiplexer (PMWDM) series product, has the characteristics of low insertion loss, high handing power, high extinction ratio and double-axis operation. It is mainly used in the fields of polarization-maintaining fiber laser, polarization-maintaining amplifier, polarization-maintaining sensing system and scientific research application.



Specification

Parameters		Unit	Values				
Pass Port	Wavelength Range	nm	960-990		1270-1350	1450-1490	1550-2590
	Max. Insertion Loss	dB	0.7		0.6		0.7
	Typ. Insertion Loss	dB	0.5		0.4		0.5
	Min. Isolation	dB	25		26		26
	Typ. Isolation	dB	30		30		30
Reflection Port	Wavelength Range	nm	1020-1100	1530-1600	1530-1600		1950-2050
	Max. Insertion Loss	dB	0.5		0.5		0.6
	Typ. Insertion Loss	dB	0.3		0.3		0.4
	Min. Isolation	dB	13		13		13
	Typ. Isolation	dB	15		15		15
Min. Return Loss		dB	50				
Min. Extinction Ratio		dB	20				
Max. Handling Power		mW	500				
Fiber Type		--	PM Panda Fiber				
Max. Tensile Load		N	5				
Operating Temperature		°C	-5 to +70				
Storage Temperature		°C	-40 to +85				

*IL is 0.3 dB higher, RL is 5 dB lower, and ER is 2 dB lower for each connector added. Connector key is aligned to slow axis.

*Above specifications are for device without connector and may change without notice.

Ordering Information

PMWDM-①-②-③-④-⑤-⑥

① Central Wavelength	② Package Dimension	③ Fiber Type	④ Fiber Length	⑤ Fiber Jacket	⑥ Connector
980/1064—pass/reflection	5.5x35	PM980-PM980 for all ports	1-1M	0-Bare Fiber	FU-FC/PC
1064/980—pass/reflection	2.5x20	PM1550/PM980-PM1550pass port/PM980 reflect port	S-Specify	1-900μm Loose Tube	FA-FC/APC
1550/980—pass/reflection	2.5X30	S-Specify		2-2mm Cable	S-specify
s-Specify	S-Specify			3-3mm Cable	