

# Polarization Maintaining 1X2 or 2X2 Fused Tap Coupler (PMTC)

Specialist in Special Optic Devices

## Introduction

Beamq **Polarization Maintaining Fused Tap Coupler (PMTC)** series product, is used to divide input polarization maintaining fiber into two outputs according to the established spectral ratio. It is widely used in the fields of fiber laser, fiber amplifier, fiber communication and fiber sensing, with compact configuration, low insertion loss, low polarization related loss and high stability.



## Specification

Parameter	Unit	Values								
Configuration	-	1X2 or 2X2								
Center Wavelength	nm	633	780	830	980	1064	1310	1550	2000	
Operating Wavelength Range	nm	±3	±10	±10	±15	±15	±20	±20	±20	
Max.PDL	dB	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.2	
Typ. Excess Loss	dB	0.8	0.5	0.5	0.4	0.4	0.3	0.3	0.5	
Max. Excess Loss	dB	1.2	0.8	0.8	0.6	0.6	0.5	0.5	0.7	
Typ. Extinction Ratio	dB	18	18	18	20	20	20	20	20	
Min.Extinction Ratio	dB	15	15	15	17	18	18	18	18	
Min.Return Loss	dB	50								
Handing Power	mW	100	200	200	300	500	2000	2000	4000	
Max. Tensile Load	N	5								
Fiber Type	-	PM630HP	PM780HP	PM780HP	PM980	PM980	PM1550	PM1550	PM1550	PM1950
Working Temperature	°C	-5 to +75 °C								
Storage Temperature	°C	-40 to +85 °C								
Coupling Ratio and Tolerance										
Coupling Ratio	%	1/99	2/98	5/95	10/90	20/80	30/70	40/60	50/50	
Tolerance	%	±0.3	±0.5	±0.7	±1.0	±2.0	±2.0	±2.5	±3.0	

\*IL is 0.3 dB higher, RL is 5 dB lower, and ER is 2 dB lower for each connector added. Connector key is aligned to slow axis.

\*Above specifications are for device without connector and may change without notice.

## Ordering Information

**PMTC-①-②-③-④-⑤-⑥-⑦-⑧**

①Center Wavelength	②Configuration	③Coupling Ratio	④Fiber Type	⑤Fiber Length	⑥Fiber Jacket	⑦Connector Type	⑧Working Axis
1064-1064nm	1×2-1×2	1/99-1/99	PM980	1-1M	0-Bare Fiber	FU-FC/PC	F-Fast Axis Blocked
1550-1550nm	2×2-2×2	10/90-10/90	PM1550	S-Specify	1-900μm Loose Tube	FA-FC/APC	B-Both Axis Blocked
2000-2000nm		50/50-50/50	S-Specify		2-2mm Cable	S-specify	S-specify
S-Specify		S-Specify					